


# LOAN DOCUMENT

			PHOTOGRAPH THIS SHEET	
DTIC ACCESSION NUMBER		LEVEL		INVENTORY
	<div style="font-size: 1.5em; font-family: cursive;">WL-TR-96-2088</div> DOCUMENT IDENTIFICATION			
	<div style="border: 1px solid black; padding: 5px; margin: 10px auto; width: 80%;">                     DISTRIBUTION STATEMENT A                      Approved for public release                      Distribution Unlimited                 </div> DISTRIBUTION STATEMENT			
ACCESSION FOR NTIS <input type="checkbox"/> GRAM <input checked="" type="checkbox"/> DTIC <input type="checkbox"/> TRAC <input type="checkbox"/> UNANNOUNCED <input type="checkbox"/> JUSTIFICATION		<div style="border: 1px solid black; height: 150px; width: 100%;"></div> DATE ACCESSIONED		
BY				
DISTRIBUTION/				
AVAILABILITY CODES				
DISTRIBUTION <div style="font-size: 1.5em; font-family: cursive;">A-1</div>		AVAILABILITY AND/OR SPECIAL <div style="border: 1px solid black; height: 50px; width: 100%;"></div>		
DISTRIBUTION STAMP		<div style="border: 1px solid black; height: 100px; width: 100%;"></div> DATE RETURNED		
<div style="font-size: 1.5em; font-family: cursive;">A-1</div> <div style="font-size: 2em; font-weight: bold;">19960812 170</div> DATE RECEIVED IN DTIC				
		REGISTERED OR CERTIFIED NUMBER		
PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-FDAC				

HANDLE WITH CARE

**WL-TR-96-2088**

**PIV Technology for Simulated Turbine Film-Cooling Flows**



**Richard Rivir  
Sivaram P. Gogineni  
Larry P. Goss  
David J. Pestian**

**September 8-10, 1996**

**FINAL REPORT 1 NOVEMBER 1995--9 JULY 1996**

**Approved for public release; distribution unlimited**

**AERO PROPULSION & POWER DIRECTORATE  
WRIGHT LABORATORY  
AIR FORCE MATERIEL COMMAND  
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7650**

**This paper is declared a work of the U.S. Government and as such is not subject to copyright protection in the United States**

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE September 8-10, 1996	3. REPORT TYPE AND DATES COVERED Final 1 Nov 95 - 9 Jul 96		
4. TITLE AND SUBTITLE  PIV Technology for Simulated Turbine Film-Cooling Flows		5. FUNDING NUMBERS  PE 61102F JON 2307S315		
6. AUTHOR(S)  R. Rivir, S. Gogineni, D. Trump, L. Goss, D. Pestian				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Aero Propulsion & Power Directorate Wright Laboratory Air Force Materiel Command Wright-Patterson Air Force Base, OH 45433-7650		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Aero Propulsion & Power Directorate Wright Laboratory Air Force Materiel Command Wright-Patterson Air Force Base, OH 45433-7650 POC: Richard B Rivir, WL/POTT, 513-255-5132		10. SPONSORING / MONITORING AGENCY REPORT NUMBER  WL-TR-96-2088		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT  APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words)  Two-color double-pulsed PIV (Particle Image Velocimetry) was used to investigate turbine film-cooling flows with high freestream turbulence and simulated wake passing. Since the instantaneous realizations of these highly turbulent and unsteady flows are not representative of mean flow behavior, 10 - 30 realizations were typically recorded. The average from these realizations of the film-cooling flows for 1% freestream turbulence was compared with the corresponding hot-wire profile. The PIV images revealed shear-layer structure developing from the film-cooling-hole walls that has not been previously considered in modeling these flows. Improved modeling of the fluid dynamics of interaction and development of these flows (jet-spread and turning) also resulted from this PIV technique.				
14. SUBJECT TERMS			15. NUMBER OF PAGES 12	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT  SAR	

## GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to ***stay within the lines*** to meet ***optical scanning requirements***.

**Block 1. Agency Use Only (Leave blank).**

**Block 2. Report Date.** Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

**Block 3. Type of Report and Dates Covered.** State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

**Block 4. Title and Subtitle.** A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

**Block 5. Funding Numbers.** To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

<b>C</b> - Contract	<b>PR</b> - Project
<b>G</b> - Grant	<b>TA</b> - Task
<b>PE</b> - Program Element	<b>WU</b> - Work Unit Accession No.

**Block 6. Author(s).** Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

**Block 7. Performing Organization Name(s) and Address(es).** Self-explanatory.

**Block 8. Performing Organization Report Number.** Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

**Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es).** Self-explanatory.

**Block 10. Sponsoring/Monitoring Agency Report Number.** (If known)

**Block 11. Supplementary Notes.** Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

**Block 12a. Distribution/Availability Statement.** Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

**DOD** - See DoDD 5230.24, "Distribution Statements on Technical Documents."

**DOE** - See authorities.

**NASA** - See Handbook NHB 2200.2.

**NTIS** - Leave blank.

**Block 12b. Distribution Code.**

**DOD** - Leave blank.

**DOE** - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

**NASA** - Leave blank.

**NTIS** - Leave blank.

**Block 13. Abstract.** Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

**Block 14. Subject Terms.** Keywords or phrases identifying major subjects in the report.

**Block 15. Number of Pages.** Enter the total number of pages.

**Block 16. Price Code.** Enter appropriate price code (*NTIS only*).

**Blocks 17. - 19. Security Classifications.** Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

**Block 20. Limitation of Abstract.** This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

# PIV Technology for Simulated Turbine Film-Cooling Flows

**Sivaram P. Gogineni**

Systems Research Laboratories, Dayton, OH 45440

**Richard B. Rivir**

Wright Laboratory, Wright-Patterson Air Force Base, OH 45433

**Larry P. Goss**

Innovative Scientific Solutions, Inc., Beavercreek, OH 45430

**David J. Pestian**

University of Dayton Research Institute, Dayton, OH 45469

**ABSTRACT:** Two-color double-pulsed PIV (Particle Image Velocimetry) was used to investigate turbine film-cooling flows with high freestream turbulence and simulated wake passing. Since the instantaneous realizations of these highly turbulent and unsteady flows are not representative of mean flow behavior, 10 - 30 realizations were typically recorded. The average from these realizations of the film-cooling flows for 1% freestream turbulence was compared with the corresponding hot-wire profile. The PIV images revealed shear-layer structure developing from the film-cooling-hole walls that has not been previously considered in modeling these flows. Improved modeling of the fluid dynamics of interaction and development of these flows (jet-spread and turning) also resulted from this PIV technique.

## NOMENCLATURE

d	film-cooling-hole diameter (1.905 cm)
R	coolant blowing (mass-flux) ratio ( $\rho_c U_c / \rho_\infty U_\infty$ )
Re	Reynolds number based on film-cooling-hole diameter
Tu	turbulence intensity ( $u'/U$ )
U	mean local streamwise velocity (m/s)
x	streamwise distance measured from the downstream lip of the injection hole (cm)
y	vertical distance from the injection surface (cm)
f	forcing frequency (Hz)
$\omega$	vorticity, $1/2(\partial V/\partial x - \partial U/\partial y)$ (1/s)
$\Omega$	reduced frequency (freestream velocity/coolant-hole diameter/oscillation frequency)

## 1 INTRODUCTION

1. PIV has been explored as an initial step for the measurement of unsteady-flow phenomena associated with the film cooling of turbine components. A detailed understanding of these unsteady flow features is important because recent trends in aircraft-engine gas-turbine combustor designs have resulted in short, high-temperature combustors which produce highly turbulent exit flows. As the exit temperature of the combustors is increased to benefit engine-cycle efficiency, effective film cooling of the turbine components downstream of the combustor becomes increasingly important. Bons et al. (1994, 1995) investigated the effect of unsteadiness and high freestream turbulence on film-cooling effectiveness using physical probes including hot wires and thermocouples. Physical probes, however, are hampered by their intrusive nature, limited spatial resolution (pointwise measurements), and spatial averaging. Hence, an effort was made to

assess PIV development and its application to the measurement of unsteady flow phenomena associated with turbine film-cooling flows.

Film-cooling air is injected through rows of small (0.5 - 0.8 mm diameter typical) holes in the blade surface. The cooling air is supplied from the compressor exit flow and is maintained at essentially constant pressure. The Reynolds numbers ( $Re$  - based on the coolant-hole diameter of 1.905 cm) investigated for the unforced flow are 20,000 and 40,000. The effect of vane wake on rotor film-cooling flow is simulated by periodic forcing of the film-cooling flows at the reduced frequency ( $\Omega$ ). Typical reduced frequencies of interest are in the range 20 - 200, which translates to 5 - 50 Hz for this large-scale experiment. Phase-locked measurements at 45-deg. increments of the periodic film forcing for freestream turbulence levels ( $Tu$ ) of 1 and 17% have been made.

PIV has been used for a number of years to measure velocity distributions in planar cross sections of aerodynamic flow fields (Adrian 1991, Lourenco et al. 1989). The advantages of the two-color PIV system used in the present investigation are 1) the directional ambiguity is resolved using the color coding of the particle images, which is inherent in the system, 2) higher data yields and signal-to-noise levels are attainable, and 3) the technique is suitable for both reacting and non-reacting flow fields. The present paper also describes extension of two-color PIV by recording the color images onto a single high-resolution (3060 x 2036 pixels) color CCD camera, thus eliminating the processing time and subsequent digitization time of color film and the complexities associated with conventional image-shifting techniques. For demonstrating the direction-resolving capabilities of this technique and comparing the resolution and accuracy of film vs CCD, a calibration test was performed using a rotating wheel (Gogineni et al. 1996a).

## 2 EXPERIMENTAL SETUP AND PROCEDURES

### 2.1 Facility description

The open-loop film-cooling wind tunnel, as shown in Figure 1, has been described in detail by Bons et al. (1994, 1995). The main flow passes through a conditioning plenum containing perforated plates, honeycomb, screens, and a circular-to-rectangular transition nozzle. Downstream of the transition nozzle, at the film-cooling station, freestream turbulence levels of 0.7% ( $\pm 0.05$ ) can be achieved, with velocity and temperature profiles being uniform to within 1%. A single row of 1.905-cm film-cooling holes at an injection angle of 35 deg. to the primary flow was investigated. The length-to-diameter ratio of the film-cooling holes evaluated is 2.4. The ratio of integral turbulence scale to film-hole diameter is in the range 2.88 - 4.23, depending on the turbulence level and turbulence-generation mechanism (Bons et al. 1994). The ratio of momentum thickness to hole diameter typically is 0.05. The ratio of micro scale to film-hole diameter is in the range 0.1 - 0.39. The ratio of temperature or density of the film flow to primary flow is typically in the range 1.07 - 1.09. The variation in blowing ratios ( $R = 0.5 - 1.5$ ) is achieved effectively by varying the ratio of the film-flow to the primary-flow velocity. For simulation of the vane-wake effects, the film-cooling jet is modulated with a speaker located in the side walls of the coolant-supply plenum.

### 2.2 Two-color PIV system

The two-color PIV system (Gogineni et al. 1996b) uses color for temporal marking of the seed particles in the flow field. For successful PIV measurements in complex three-dimensional flows, the selection and implementation of the proper seeding strategy is a major factor. The seeding particles must be extremely small (typically  $< 1 \mu m$ ) to track accelerations in the fluid effectively. In the present experiment, the film-cooling flow is seeded with sub-micron size particles. The green (532-nm) laser output from a frequency-doubled Nd:YAG laser and the red (640-nm) laser output from a Nd:YAG-pumped dye laser (DCM dye) are combined by a dichroic beam splitter and directed

through sheet-forming optics. The laser-sheet energy is typically 20 mJ/pulse, with a thickness of  $< 1$  mm at the test section. The temporal delay between the two lasers is dependent upon the flow velocity, optical magnification, and interrogation spot size. It is set at  $\sim 12 \mu\text{s}$  for  $\text{Re} = 20,000$ . A 105-mm micro lens with an f-number of 5.6 is used to record the images. The high-resolution CCD system (each pixel being  $9 \mu\text{m}$  square) allowed optimization of the seeding density for obtaining high-quality PIV images. The details of the CCD system, data analysis, uncertainty analysis, and calibration have been described previously by Gogineni et al. (1996a).

### 3 RESULTS AND DISCUSSION

Turbine-blade film cooling takes place in a very hostile, unsteady environment where velocity and temperature disturbances exceed 20%. The freestream and film-cooling wall conditions in these flows exceed those encountered in a classical fully turbulent boundary layer. Parameters of interest in this problem include jet spread or film effectiveness,  $R$ ,  $\text{Re}$ ,  $Tu$ , and  $\Omega$ . Accurate modeling of these flows has proved difficult due to the high-level unsteadiness. Gogineni et al. (1995, 1996b) used the two-color PIV technique to examine the region around the film-cooling hole for 3 diameters downstream and to document the penetration of the film jet, the shear-layer characteristics, and the jet spread for various flow conditions. It was shown that at  $\text{Re} = 20,000$ , turbulence clearly increases the film spread for  $R = 0.7$ . An increased jet spread results in more rapid mixing out of the film-cooling flow. When  $R < 1.0$ , it is observed that the shear-layer roll up is the reverse of what would normally be expected. This reverse roll up is attributed to the film-cooling wall boundary layer. A linear relationship between the jet-exit slopes and both  $Tu$  and  $R$  was also documented for  $R < 1.0$ .

In the present experiment, nominally 10 - 30 instantaneous images were obtained for a given flow condition to capture the essence of the flow features and to determine the time-averaged distribution. One of the main problems in utilizing film for PIV measurements is the inability to maintain the absolute coordinates of the recorded features during the digitization process. This occurs because the film cannot be consistently loaded into the film-scanner to the degree required for reproducibility. Thus, a feature in the film flow must be used as a reference or, as in this study, a correlation technique must be used to minimize the difference in the velocities as a function of image overlap. In the latter approach, one of the instantaneous images is chosen as a reference. Each image at a given flow condition is processed and the resulting velocity vectors compared to those of the reference image. The velocity vectors of each image are shifted with respect to the reference-image vectors and the velocity differences calculated. The image coordinates chosen are those which coincide with the image shifts necessary to produce the minimum velocity difference between the shifted and the reference image. This problem is completely eliminated when using a digital color CCD because no film digitization is required. The performance of a Kodak color CCD for PIV measurements in this experiment is discussed later.

Figure 2 shows a comparison of velocity data obtained with a hot-wire probe and the PIV technique at unforced flow conditions ( $x/d = 1$ ,  $\text{Re} = 20,000$ ,  $R = 0.7$ , and  $Tu = 1\%$ ). The horizontal bars plotted over the PIV results represent the total scatter in velocities observed for an average of 5, 10, 20, and 30 samples. The wide scatter is due to the high Reynolds number, high turbulence levels, and the large-scale turbulent structures of the film-cooling flow. Reasons for the discrepancies shown in Fig. 2 are currently under investigation. However, since only the film-cooling flow was seeded in this experiment, the velocities obtained in the interface region of the unseeded high-speed freestream and the seeded slower-speed film-cooling flow would be expected to deviate from those obtained with a hot-wire probe which cannot distinguish between the two flows. In an earlier experiment for low-Reynolds-number flow where both the ambient freestream and the jet flow were seeded, Gogineni (1993) found excellent agreement between the hot-wire data and the averaged data from 30 PIV samples. In the present experiment, one could argue that 30 images is not sufficient for accurate determination of the mean and

fluctuations of this highly unsteady flow field. For investigating this aspect, the rms fluctuation was measured at a constant flow condition, and the results show that the rms deviation approaches 20% as the number of samples is increased. However, a greater number of samples is required to represent the mean flow behavior.

For studying the characteristics of a turbine-blade film-cooling hole environment, the jet injection hole was scaled up by a factor of 35. The stator-wake passage was simulated by periodic forcing of the film-cooling flow at the appropriate reduced frequency ( $\Omega$ ), as described in Bons et al. (1995). Figure 3 shows the results for the simulation of the effect of the stator wake on the film-cooling flow when the film is forced at 20 Hz. These results were recorded on 35-mm film and digitized using a Polaroid SprintScan 35 scanner having a resolution of 2700 pixels/in. This provided a resolution of  $\sim 3000 \times 2000$  pixels. These exposures were phase locked to the film-cooling driving frequency, and data were recorded at phase-angle increments of 45 deg. in one forcing cycle. Figure 3 shows the double-exposed PIV images and the corresponding instantaneous velocity distributions at phases of 90 and 180 deg. for  $R = 0.7$ ,  $Re = 20,000$ , and  $Tu = 1\%$ . The dropouts of velocity vectors in this figure are caused by lack of particles, out-of-plane motions, and unoptimized parameters such as laser-sheet intensity and seeding density. Additional results were reported in detail by Gogineni et al. (1996c).

To overcome some of the obstacles encountered in the film-based PIV and to achieve a quick turn-around time for conducting the experiments under various conditions, a high-resolution Kodak DCS 460 CCD system was implemented. With this system it was possible to optimize the seeding and laser-sheet intensity in near real time, with the net effect being more valid vectors as well as much better definition and resolution of the shear layer. These features are illustrated in Figures 4 and 5, which correspond to unforced film flow at freestream  $Tu$  levels of 1 and 17% for  $R = 0.7$  and 1.5. The film-cooling Reynolds number is 40,000. The photographs in Figure 4 have a resolution of  $3060 \times 2036$  pixels--approximately the same as those obtained with 35-mm film after digitization. At this higher  $Re$  number, the shear-layer frequency over the film hole increases dramatically. When  $Tu$  is increased from 1 to 17% for  $R = 0.7$ , no significant change is observed in the eddy sizes in the shear layer after the film-cooling hole. However, for  $R = 1.5$ , a significant change takes place. When  $R$  is increased from 0.7 to 1.5 at a freestream  $Tu$  level of 17%, the roll-up frequency for the shear layer after the film-cooling hole decreases. In the leading-edge exit region of the film-cooling hole, a second parallel shear layer can be detected which may be associated with a separation from the entrance lip of the film-cooling hole, as illustrated in Figures 4(a), 4(b), and 4(c).

Figure 5 shows the instantaneous velocity distribution corresponding to that in Figure 4 which was obtained using a cross-correlation technique (Gogineni et al. 1996c). For improving analysis of the seeded flow field, the output of the linear camera was convolved with a logarithm-like function prior to the cross-correlation analysis. The interrogation domain measured  $64 \times 64$  pixels, corresponding to  $2 \times 2$  mm in the measured flow. For enhancing the overall resolution, the interrogation domains are overlapped by one-half the domain size. For clarity purposes, only one-third of the measured vectors (raw data) are shown in each frame and no post-processing such as interpolation is implemented for these data. The velocity field shown here corresponds to the fixed reference frame; thus, the shear-layer structures are not visible. The large vertical components of the counter-rotating vortical structures formed by the interaction with the freestream can be seen in Figure 5 underneath the shear layer.

Figure 6 shows the vorticity distribution ( $\omega$ ) computed by central differencing of the velocity field of Figure 5. The solid lines indicate positive vorticity, and the dashed lines indicate negative vorticity. As expected, high values of vorticity are found in the shear layer and in the film layer at lower  $R$ . When  $R$  is increased to 1.5 and  $Tu$  to 17%, the vorticity is concentrated in the shear layer far from the surface. The vorticity distribution from the CCD data showed a significant improvement over that resulting from the 35-mm film data (not shown). This can be attributed to the presence of the more valid vectors that resulted from the optimization of PIV parameters.

## CONCLUSIONS

Turbine film-cooling data from 35-mm film after digitization and from a 3060 x 2036 pixel CCD camera have been compared and found to have similar spatial resolutions. The CCD allowed optimization of seeding and laser-sheet intensity which resulted in higher vector densities. Hot-wire data and the average of more than 20 PIV frames at  $x/d = 1$  agreed favorably for these highly unsteady flows; however, direct use of mean values for these flows would require an average of more than 30 samples.



PIV has proved to be extremely useful in obtaining additional information on the structure of turbine film-cooling flows such as jet spread, shear-layer growth, and shear-layer frequency. PIV also allows the computation of realizations of vorticity and dissipation for direct comparison with CFD data. PIV has revealed significant changes at the exit of the film hole, reinforcing the importance of modeling flows in these short  $l/d$  film-cooling holes.

## ACKNOWLEDGMENTS



This work was performed under partial sponsorship of the Air Force Office of Scientific Research Project 2307S, with Dr. James McMichael as program manager. The work was also supported by Wright Laboratory, Aero Propulsion and Power Directorate, Wright-Patterson Air Force Base, Ohio, under USAF Contract Nos. F33615-90-C-2033 (with SRL) and F33615-95-C-2507 (with ISSI). The help of Darryl Trump (SRL) and the editorial assistance of Marian Whitaker (ISSI) are greatly appreciated.

## REFERENCES

- Adrian, R. J. 1991. Particle imaging techniques for experimental fluid mechanics. *Ann. Rev. Fluid Mech.* 23:261-304.
- Bons, J., MacArthur, C., and Rivir, R. 1994. The effect of high freestream turbulence on film cooling effectiveness. ASME 94-GT-51, 39th International Gas Turbine and Aeroengine Congress and Exposition, The Hague, Netherlands.
- Bons, J., Rivir, R., Mac Arthur, C., and Pestian, D. 1995. The effect of unsteadiness on film cooling effectiveness. AIAA 95-0306, 33rd Aerospace Sciences Meeting and Exhibit, Reno NV.
- Gogineni, S. 1993. Particle image velocimetry study of two dimensional transitional wall jet. Ph. D. Thesis, Florida State University, Tallahassee, Florida.
- Gogineni, S., Rivir, R., Pestian, D., and Goss, L. 1995. High freestream turbulence influence on turbine film cooling flows. Winner of the 13th Annual Fluid Mechanics Gallery of Fluid Motion Photo Contest; 48th APS/DFD Annual Meeting, Irvine, CA (to be published in a special issue of *Phys. Fluids* in September 1996).
- Gogineni, S., Trump, D., Goss, L., Rivir, R., and Pestian, D. 1996a. High resolution digital two-color PIV (D2CPIV) and its application to high freestream turbulent flows. 8th International Symposium on Applications of Laser Techniques to Fluid Mechanics, Lisbon, Portugal.
- Gogineni, S., Rivir, R., Pestian, D., and Goss, L. 1996b. PIV measurements of flat plate film cooling flows with high freestream turbulence. AIAA 96-0617, 34th Aerospace Sciences Meeting and Exhibit, Reno NV.
- Gogineni, S., Trump, D., Pestian, D., and Rivir, R. 1996c. PIV measurements of periodically forced flat plate film cooling flows with high freestream turbulence. 1996 ASME International Gas Turbine and Aeroengine Congress/Users Symposium and Exposition, Birmingham, UK.
- Lourenco, L. M., Krothapalli, A., and Smith, C. A. 1989. Particle image velocimetry. In M. Gad-el-Hak (ed), *Advances in Fluid Mechanics Measurements*:127-199. Berlin: Springer-Verlag.



Double exposed PIV images



Instantaneous velocity distribution

Figure 3. Simulated turbine vane wake ( $Re = 20,000$ ,  $R = 0.7$ ,  $Tu = 1\%$ ,  $f = 20Hz$ )







Figure 4. Simulated turbine film-cooling flows using CCD sensor ( $Re = 40,000$ )  
(Double exposed PIV images)




Figure 5. Instantaneous velocity distribution (Re = 40,000)




Figure 6. Instantaneous vorticity distribution (Re = 40,000)